



**"J"-HOOK**

PIN		
SIZE	*D	L
10GA	.135	AS REQUIRED

\* Other diameters available upon request.

<b>MATERIAL:</b> <b>LOW CARBON STEEL</b> C - 0.23% max. P - 0.04% max. Mn - 0.90% max. S - 0.05% max.	<b>STAINLESS STEEL</b> AISI grade - 302/304/305 std. Other grades available upon request.
<b>MECHANICAL PROPERTIES:</b> Tensile 60,000 psi (min.) Yield 50,000 psi (min.) Elongation 20% (in 2 inches)	Values for various grades available upon request.
<b>PLATING:</b> Copper coating is standard.	Does not apply to Stainless.
<b>ANNEALING:</b> Can be annealed where required.	Can be annealed if required.

**APPLICATION:** This is the standard insulation fastener used to secure insulation to wire road mesh.

**WASHERS:** Self-locking washers are available in a variety of sizes, shapes, and materials.

**TO ORDER OR SPECIFY GIVE:**

1. Product Code . . . . . JH
2. Size . . . . .
3. Length . . . . . L
4. Material . . . . .

**NEW-AGE**  
**FASTENING SYSTEMS, INC.**

Studwelding Equipment, Fasteners & Supplies  
Boiler Outage Specialists  
Jobsite Studwelding Division  
P.O. Box 5658, Deptford, NJ 08096  
Phone: (856) 218-8301  
Fax: (856) 218-8305  
Toll Free: (888) 889-3833  
steve@newagestudwelding.com

All information contained herein subject to change without notice.