



“SURE-FIRE” (CD)

SIZE	PIN		
	D	L	FD
12GA	.105	AS REQUIRED	.175
10GA	.135	AS REQUIRED	.195

MATERIAL: LOW CARBON “MILD” STEEL C - 0.23% max. P - 0.04% max. Mn - 0.90% max. S - 0.05% max.	STAINLESS STEEL AISI grade - 302/304/305 std. Other grades available upon request.
MECHANICAL PROPERTIES: Tensile 60,000 psi (min.) Yield 50,000 psi (min.) Elongation 20% (in 2 inches)	Values for various grades available upon request.
PLATING: Galvanized coating is standard on pins.	Does not apply to Stainless.
ANNEALING: Can be annealed if required.	Can be annealed if required.

APPLICATION: Ideally suited for welding to surfaces covered with mill scale, rust, or paint.

WASHERS: Self-locking washers are available in a variety of sizes, shapes, and materials.

TO ORDER OR SPECIFY GIVE:

1. Product Code SF
2. Size
3. Length L
4. Material

All information contained herein subject to change without notice.

NEW-AGE
FASTENING SYSTEMS, INC.

Studwelding Equipment, Fasteners & Supplies
Boiler Outage Specialists
Jobsite Studwelding Division
P.O. Box 5658, Deptford, NJ 08096
Phone: (856) 218-8301
Fax: (856) 218-8305
Toll Free: (888) 889-3833
steve@newagestudwelding.com