


CUP HEAD PIN (CD)



| TYPE | D | WD | MIN. | MAX. |
|------|------|-------|------|---------|
| | | | L | L |
| CS12 | .105 | 1.187 | 3/8 | NO MAX. |
| CS14 | .080 | 1.187 | 3/16 | NO MAX. |

| PIN | WASHER |
|--|---|
| MATERIAL: LOW CARBON STEEL C - 0.23% max. P - 0.04% max. Mn - 0.90% max. S - 0.05% max. | LOW CARBON STEEL C - 0.23% max. P - 0.04% max. Mn - 0.90% max. S - 0.05% max. |
| MECHANICAL PROPERTIES: Values available upon request. | Values available upon request. |
| PLATING: Galvanized coating is standard on pins. | Standard Washer is galvanized. |
| BEVEL: Washer edge is beveled to prevent cutting of insulation material. | |
| STAINLESS STEEL: Not standard, but available by special order. | |

PAPER INSULATING WASHERS:

Available for welding through foil faced insulation.
Paper insulating washers can be ordered separately or factory installed.

TO ORDER OR SPECIFY GIVE:

1. Product Code CHSW
2. Size
3. Length L
4. Material

All information contained herein subject to change without notice.

NEW-AGE
FASTENING SYSTEMS, INC.

Studwelding Equipment, Fasteners & Supplies

Boiler Outage Specialists

Jobsite Studwelding Division

P.O. Box 5658, Deptford, NJ 08036

Phone: (856) 218-8301

Fax: (856) 218-8305

Toll Free: (888) 889-3833

steve@newagestudwelding.com